Destol F-Ⅱ

Mold sludge prevention additive for MDO and MGO

Destol F-Ⅱ is a fuel additive for MDO and MGO (hereinafter FO) that prevents mold growth and the sludge troubles it causes, simply by mixing the additive with FO.

Characteristics

●Appearance:	Colorless～light yellow transparent liquid
●Density:	0.85 g/cm^3 (15℃)
●Viscosity:	5.8 cSt (50℃)
●Flash Point:	80℃ (TAG)
●Main components:	Nitrogenous substance, petroleum solvent

Advantages

- ○ It suppresses a mold growth caused of sludge troubles.
- ○ It prevents growth of mold mycelium that has already grown up.
- ○ The effect lasts for long term.
- ○ It can dissolve and disperse easily in FO, and it has no negative effect on combustion.

Direction for use

We recommend adding the additive to the FO storage tank before bunkering to ensure it mixes well with FO.

The addition rate will vary depending on the usage situation; please refer to the following table.

① Standard addition rate for bunkering:	Please dose it into the storage tank at a dilution of 1/5,000 before bunkering.
② Periodic addition rate for maintenance:	Please dose it into the storage tank at a dilution of 1/5,000 if more than one year has passed since the previous bunkering or dosing.
③ When a mold sludge confirmed:	Please feel free contact to our sales department. E-mail:sales-one@nipponyuka.com

(Continued on Reverse Side)

2025.02

Cautions for use

- ○ Do not use this product in ways not described in the instructions for use.
- ○ Flammable liquid, keep away from open flames.
- ○ Wear respirator, goggles, and resistant rubber gloves.
- ○ First-aid procedure:
  - Eye contact: Wash with plenty of fresh clean water more than 15 minutes.
  - Skin contact: Wash with soap and fresh water. Apply skin cream.
  - Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing.

※Please consult a doctor as needed.

Cautions for storage

- ○ Do not transfer the product to other containers as this may cause deterioration in quality.
- ○ Keep away from open flames.
- ○ Store in cool and dark place.

Container

	NET (L)	Weight (kg)	Size (W×D×H cm)
●200L Drum	200L	191.7	φ58.5×89
●18L Can	18L	16.5	23.8×23.8×35



NIPPON YUKA KOGYO CO., LTD.
Head Office : TEL : (+81)-45-201-8867 / FAX : (+81)-45-201-8358
Kobe Branch : TEL : (+81)-78-321-4105 / FAX : (+81)-78-321-4107

←You can contact us here!
(https://www.nipponyuka.jp/)

