Yunisol H

Oil sludge remover

Yunisol H is a very effective detergent to remove oily carbon on oil heater, LO cooler and pipe line.

Characteristics

- Appearance : Transperent liquid
- Density : 0.903 g/cm^3 (15°C)
- Flash Point : 65°C (PM)
- Reaction : Neutral

Advantages

- Yunisol H is a carbon remover by high penetration and dissolving power.
- It is a neutral agent and has no damage to metal.

Direction for use

- Yunisol H is used in straight. Don't dilute by any solvent.
- The soaking method

  In case of small machine parts, soak the parts in Yunisol H for 10-30 minutes and wipe or wash in water.
- Poultice method

  Soak cloth into Yunisol H and attach it to the stained parts for 30-60 minutes and wipe off.
- Circulation cleaning method

  1) Connect a temporary hose or piping.

  2) Using a pump with appropriate volume and circulate Yunisol H for 2 to 10 hours. Cleaning time depends on the type of carbon and condition of tough sluge.

  3) Warming Yunisol H if required, by admitting steam on the steam side of the exchanger. Don't heat to over 60°C.

Safety and handling

- Use the material of the oil-proof hose/tube to be used for circulation cleaning.
- Wear suitable protective clothing, gloves and eye/face protection.

First-aid procedure

・If product gets into eyes, immediately rinse them with water for 15 min.

※ Submit to medical treatment situationally.

Container


	Wight,kg	Size, (WxDxH,cm)
● 18 litter can	17.4	23.8x23.8x35



NIPPON YUKA KOGYO CO., LTD.

Head Office : TEL : (+81)-45-201-8867 / FAX : (+81)-45-201-8358
Kobe Branch : TEL : (+81)-78-321-4105 / FAX : (+81)-78-321-4107

←You can contact us here!
(https://www.nipponyuka.jp/)



2023.08